

housings Plus M 3P SX

with 2 manometers for cartridges with standard flat seals



Medium M Junior M Master M Senior M

APPLICATIONS

Filtration and treatment of water with neutral pH and drinking water. The housings provided with 2 manometers allow the perfect control on pressure drop and define the proper timing for filter cartridges maintenance, as washing or changing the cartridge.

Domestic use: filtration and treatment of drinking water, protection of taps, boilers, washing machines, and other installations.

Technical use: pre-filtration, micro-filtration; protection of pumps, heating systems, softeners, demineralising and chlorine-removing appliances, reverse osmosis units.

Remark: change or wash the filter cartridge before the differential pressure of 1 BAR to avoid possible cartridge collapse.

WORKING CONDITIONS

Max working pressure _____ 8 BAR
Max working temperature _____ 45°C

SPECIFICATIONS

Non-toxic materials, suitable for drinking water.

Head and ring nut: reinforced polypropylene.

Transparent bowl: SAN.

O-ring: EPDM.

Breather-valve: body polypropylene, O-ring EPDM.

IN/OUT threads: CW 614 N brass inserts.

Manometers: radial type, pressure range BAR 0-12, PSI 0-170.

Cartridge height	housings with 2 manometers with transparent bowl AS IN/OUT female threads with FO brass insert	IN/OUT threads	mm	
			A	B
5"	Medium Plus M 3P MFO SX AS	1/2"	241	133
5"	Medium Plus M 3P AFO SX AS	3/4"	241	133
5"	Medium Plus M 3P BFO SX AS	1"	247	145
7"	Junior Plus M 3P MFO SX AS	1/2"	291	133
7"	Junior Plus M 3P AFO SX AS	3/4"	291	133
7"	Junior Plus M 3P BFO SX AS	1"	297	145
10"	Senior Plus M 3P MFO SX AS	1/2"	365	133
10"	Senior Plus M 3P AFO SX AS	3/4"	365	133
10"	Senior Plus M 3P BFO SX AS	1"	371	145
20"	Master Plus M 3P MFO SX AS	1/2"	621	133
20"	Master Plus M 3P AFO SX AS	3/4"	621	133
20"	Master Plus M 3P BFO SX AS	1"	627	145



VARIANTS available on minimum quantity

AB housings with opaque bowl, impermeable to the light.



BX housings for quick-fit cartridges with double O-ring.



S bowl with discharge ball-valve for self-cleaning (only for Senior BX type).



accessories



-U- Spanner



-S- wall bracket



wall bracket screws



3/4" and 1" brass nipples with O-ring



5", 7", 10" diffuser tubes

housings Plus M 2P SX

with 2 manometers for cartridges with standard flat seals



Cadet M

Junior M

Senior M

APPLICATIONS

Filtration and treatment of water with neutral pH and drinking water. The housings provided with 2 manometers allow the perfect control on pressure drop and define the proper timing for filter cartridges maintenance, as washing or changing the cartridge.

Domestic use: filtration and treatment of drinking water, protection of taps, boilers, washing machines, and other installations.

Technical use: pre-filtration, micro-filtration; protection of pumps, heating systems, softeners, demineralising and chlorine-removing appliances, reverse osmosis units.

Remark: change or wash the filter cartridge before the differential pressure of 1 BAR to avoid possible cartridge collapse.

WORKING CONDITIONS

Max working pressure _____ 8 BAR
Max working temperature _____ 45°C

SPECIFICATIONS

Non-toxic materials, suitable for drinking water.

Head and ring nut: reinforced polypropylene.

Transparent bowl: SAN.

O-ring: EPDM.

Breather-valve: body polypropylene, O-ring EPDM.

IN/OUT threads: CW 614 N brass inserts.

Manometers: radial type, pressure range BAR 0-12, PSI 0-170.

Cartridge height	housings with 2 manometers with transparent bowl AS IN/OUT female threads with FO brass insert	IN/OUT threads	mm	
			A	B
4"	Cadet Plus M 2P MFO SX AS	1/2"	219	133
4"	Cadet Plus M 2P AFO SX AS	3/4"	219	133
4"	Cadet Plus M 2P BFO SX AS	1"	225	145
7"	Junior Plus M 2P MFO SX AS	1/2"	291	133
7"	Junior Plus M 2P AFO SX AS	3/4"	291	133
7"	Junior Plus M 2P BFO SX AS	1"	297	145
10"	Senior Plus M 2P MFO SX AS	1/2"	365	133
10"	Senior Plus M 2P AFO SX AS	3/4"	365	133
10"	Senior Plus M 2P BFO SX AS	1"	371	145



VARIANT available on minimum quantity

AB housings with opaque bowl, impermeable to the light.



accessories



-U- Spanner



-S- wall bracket



wall bracket screws



3/4" and 1" brass nipples with O-ring



4", 7", 10" diffuser tubes